


Specialist Hinges


Double Action Hinges, Pivot Hinge Sets, Concealed Hinges



Double Action Spring Hinges for Restaurant Kitchen Doors and Saloon Doors

INLDA04 Liobex 100mm Hinge (Pair) in Silver

INLDA06 Liobex 150mm Hinge Pack in Silver
Contains 3 hinges and intumescent pack for Fire Doors 

LIODA08SE Liobex 200mm Fire Door Hinge Silver 

We strongly recommend using the right double action spring hinge to suite the door type and usage;

150mm to suit 40kg fires doors 850mm wide and 44mm thick

200mm to suit 55kg fire doors up to 1000mm wide & 54mm thick



Free Swing Pivot Hinge Sets and Emergency Door Release



Manufactured from Stainless Steel (Grade 304) and incorporates a ball bearing in the lower pin to provide smooth operation. Designed for use in lightweight and residential doors wherever the ill or infirm run the risk of falling over and blocking an inward opening toilet or bathroom door.
ref: INDAPS



Allows double action door to operate as a single swing, when hung on pivots
Emergency access is gained by depressing the stop and pulling the door outwards
Includes hold back facility
Stop release resets automatically

Argenta Concealed Hinges

The Argenta Invisible NEO is a series of hinges with an exceptionally high and sublime finish: Not a single screw is visible.

You can adjust these hinges with precision easily, flexibly, and quickly, thanks to the built-in height-adjustment system. This unique system means you no longer need to put any wedges under the door to set the height. The hinge casing in the door can be assembled beforehand in the workshop.

- Pure and qualitative design
- No visible screws
- 3 sizes available: S-5, M-6 (FD30 Available) & L-7 (FD30 & FD60 Available)
- Universal: For Left and Right hand opening doors
- "Easy-Hook": Installation and 3D adjustable by one person
- Extra simplified height adjustment: No wedge required
- 180 Degree opening angle
- 3D adjustable (height, width, and depth) without taking the door off

Invisible NEO S-5

- Door Thickness: min. 33 mm
- Door Weight (2 pcs) : up to 60kg
- Door Weight (3 pcs) : up to 80kg
- Height Adjustment: -2,5 / +2,5 mm
- Width Adjustment: -3,0 / +4,0 mm
- Depth Adjustment: -1,0 / +1,0mm
- Fire Resistant: EI30 (NEO-S5 EI30/Finish*) 3 hinges required
- Screw Dia: max. 4.5



EI30